







MAXIMUM SPAN DISTANCE			
Thickness	No Sections	T Section	H Section
25 mm	<1300 mm	1400 – 1800 mm	1900 – 2800 mm
30 mm	<1400 mm	1500 – 1800 mm	1900 – 2800 mm
40 mm	<1800 mm	1900 – 2100 mm	2200 – 2800 mm
50 mm	<2000 mm	2100 mm	2200 – 2800 mm
60 mm	<2000 mm	2100 mm	2200 – 2800 mm
70 mm	<2200 mm	2300 – 2500 mm	
80 mm	<2200 mm	2300 – 2500 mm	No H Sections available
90 mm	<2200 mm	2300 – 2500 mm	

- H & T Sections available sizes 30mm 60mm
- LAMBDABOARD® H & T Sections are to be used in conjunction with LAMBDABOARD® Insulation Boards to obtain the COC
- Standard H & T Section lengths are 6m
- $\bullet$   $\:$  All H & T Sections colour match to the LAMBDABOARD  $^{\otimes}$  White Mineral Colour
- We also provide a cutting list or cutting service for all LAMBDABOARD® orders.

WON'T MELT OR DRIP when exposed to flames

LAMBDABOARD® H SECTION

LAMBDABOARD® T SECTION