

ULTRASEAL CEMENTITIOUS



**ULTRA
SEAL**
THE WATERPROOFING CHOICE



Weather
Resistant



Durable &
Flexible



UV
Stable

Ultraseal Cementitious is a two component elastomeric waterproofing coating with added fiber.

Manufactured by NUI – Member of the RIGIFoam Group

ULTRASEAL CEMENTITIOUS



Ultraseal Cementitious is a two component elastomeric waterproofing coating with added fiber.

Ultraseal Cementitious is highly elastic with exceptional adhesion properties that can be used to waterproof:

- Concrete structures, storage tanks, pipes, basements, water canals, bridges and both internal and external walls and floors against hydraulic pressures.
- Balconies, showers and under tiled applications.
- Water features, fountains, swimming pools, ponds and sewage treatment plants.
- Protection of new and old exposed concrete against carbonation, chloride and sulphate attack.

ADVANTAGES





- Highly flexible with crack bridging capabilities.
- Excellent adhesion to most masonry substrates.
- Non-toxic to water, plants and fish

APPLICATION

Keep substrate moist during application. **Ultraseal Cementitious** can be applied by trowel, roller, brush or mechanical spray equipment. Apply at a minimum of 1.5 mm per coat. Use Geo-membrane (membrane approved by N.U.I. only) to cover cracks or highly stressed areas embedded into the base coat mortar.

Application method:

Apply two sealing coats and one tack coat. The two sealing coats must be applied at right angles. Ensure that the 1st coat is completely dry before applying the 2nd coat (usually 2 – 6 hours). Leave the sealing coats to dry for 48 hours then apply the tack coat. Water retaining structures, should cure or for 7 days before adding water.

<p>TOUCH DRY</p>  <p>± 3 hours</p>	<p>FULL CURE</p>  <p>2 days</p>	<p>OVER-COATING</p>  <p>2 – 6 hours</p>	<p>AVERAGE COVERAGE*</p>  <p>3 - 5 m² / Kit</p>
---	--	--	---



APPLICATION METHODS



Manufactured by NUI – Member of the RIGIFoam Group

www.ultraseal.co.za
www.rigifoam.co.za
 +27 (0)11 421 0313



DISAVOWAL: The customer acknowledges and understands that after delivery, the goods will have left the control of Rigifoam (Pty) Ltd, and that the customer will be responsible for the unpacking of and connection/installation of the goods. The customer acknowledges that it is his/her further responsibility to ensure that a fully qualified and competent person is used to install the goods to ensure their effective operation. Failure by the customer to ensure the installation of the goods, according to the written instructions of the manufacturer and/or supplier, by a fully qualified and competent person, may result in the failure of the goods, injury, loss or damages to the customer. Accordingly, and in this event, Rigifoam (Pty) Ltd accepts no responsibility for any loss or damages that might arise by reason of death or personal injury to any person engaged in the installation or use of the goods thereafter, subject to the provisions of the Consumer Protection Act 68 of 2008.